

✓ ez-Wheel® autonomous wheel ezW10R/W - Series 10"
✓ developed for the outdoors
✓ suitable for:

- delivery carts
 - street trolleys
 - land drones
 - (...)

Component specifications

Motor

Technology	BLDC PM
Gearbox	1-stage helical
Indicative lifespan*	5 000 h / 15 000 km 1 500 000 starts/stops
Nominal speed	135 rpm (10 km/h)
Nominal power	250 W (S1 à 10 km/h)
Peak torque	52 Nm

Battery

	÷
Electrochemistry	Ni-MH long life
Energy	240 Wh
Indicative lifespan*	5-8 years
Recharge mode	Charger
Minimum charging time*	2h30 hours (to 90%)

Interface

Wired	-
Wireless	LR WPAN 2.4 GHz IEEE 802.15.4

All values are subject to changes without prior notice.

ez-⊎hee

*: Values for reference, based on standard condition testing, may vary with different application cases.



VCert. 73599

Technical characteristics

Diameter	400 mm
Type of Tyre	10x4 - Road tyre
Speed range (traction)	0 to 15 km/h
Peak pushing effort	-
Nominal performance	250 W à 10 km/h
Maximum rolling speed	18 km/h
Battery capacity	240 Wh
Option(s)	-

Conditions of use

	•
Temperatures	-20 to +60 °C
IP index	IP54
Maintenance period*	5 years

The wheel can be used inside or outside, over a wide range of temperatures. The components – including the battery – do not need any inspection or maintenance over the product's whole lifespan.

Weight

	(Ad)
Wheel weight	14.5 kg
Maximum vertical load	150 kg per wheel (on a 10% slope)

The robust assembly can withstand the stresses of knocks and severe vibration and enables the wheel to carry some load.

ez-Wheel products are guaranteed 1 year from the date of purchase and 2 years against production defects. Consult the general conditions of sale for more information.

♥ Le Moulin de l'Abbaye, 135 Route de Bordeaux, 16400 La Couronne - FRANCE x info@ez-wheel.com ♥ +33 531 615 580



 (\mathbf{P})

(in)

Æ

PR